

Okta as Identity Provider for Worklytics (Single Sign-On)

The Worklytics App for Okta provides Single Sign-On (SSO) user authentication to access Worklytics, so you can use the credentials for your company's organization in Okta to log into your Worklytics account.

Background

The Worklytics platform collects and analyzes *workplace data* at the instruction of Customer Organizations on their behalf, in accordance with our Privacy Policy, Terms of Service, and any customer agreement / laws / regulations which may supersede those terms. The Customer Organization remains the controller of this data and may instruct Worklytics to halt processing and destroy it at any time.

Prerequisites

In order to add Okta as SSO provider, you have to be an administrator of your Worklytics account to complete the installation. You also need administrator rights of your Okta organization. If you don't have a Worklytics account, you can sign up here or contact our support team to get information on how to proceed.

Supported Features

The current version of the Worklytics App for Okta, supports two login flows:

- Service Provider Initiated (SP-initiated) SSO. This option gives your end-users the ability to log into the Worklytics Login page using their Identity Provider credentials (your company's organization in Okta).
- Identity Provider Initiated (IdP-initiated) SSO. This option allows your end-users to log into Worklytics directly from Okta, without having to go to the Worklytics login page.

How to integrate Worklytics with Okta SSO

Step 1: Add Worklytics App to Okta

1. Log in to Okta as an Administrator.

2. In your end-user dashboard, choose Applications then click on Browse App Catalog.

← Back to Applications

Browse App Integration Catalog

3. In the **Search for an Application** field, search for "Worklytics". When Worklytics' Okta-Verified OIDC appears, click on **Add**.

CATEGORIES		
All Integrations	7146	Q Worklytics
Analytics	644	Search results for "Worklytics"
Collaboration and Productivity	1274	ocarcinesuits for worklytics
Developer Tools	629	Single Size On
Directories and HR Systems	379	Single sign-On
Data Privacy and Consent Management	6	Worklytics Worklytics analyzes how your organization collaborates and gets work done in order to make recommendations on how you can
Identity Proofing	5	OIDC
Identity Governance and	12	
Administration		
CRM and Marketing	726	

Create New App

- 4. Now, on the **General Settings** page, you can type a name for the new application. For example: "Worklytics".
- 5. Use the option **Assign to People**, to assign those users that you want to have access to your Worklytics account.

\checkmark	Active View Log	s Monitor Imports		
eneral Si	gn On Mobile Import Assi 	gnments Okta API Scopes		
Assign 🔻	Convert assignments 🔻	Q Search People ▼	REPORTS	
ilters	Person	Туре	Current Assignments	
People Groups	John Doe john@company.com	Individual 🛛 🗡 🗙	₩ Recent Unassignments	
			SELF SERVICE	
			Requests Disabled	
			Approval -	
			Edit	

Step 2: Configure Okta as Identity Provider in Worklytics

- 1. Log in to Worklytics as an Administrator (SecurityAdmin role).
- 2. Go to he "Settings" page and choose the Single Sing-On tab.
- 3. Now, in the "Identity Providers" section, click on Add Identity Provider
- 4. You will be prompted with different options, choose Okta.
- 5. Complete the configuration by entering the following values that you'll find on the "Sign On" tab of the Worklytics application in Okta:
 - Client ID
 - Client secret: this is a private value that you must not share with anyone else.
 - Okta domain: your organization domain in Okta (example: my-company.okta.com).

\checkmark		Active	•		View Logs Monito	r Imports			
eneral	Sign On	Mol	oile	Import	Assignments	Okta	API Scope	es	
Setting	S								Edit
Sign on	methods								
The sign	-on method	determi	nes hov	w a user si	gns into and manag	ges their c	redentials	for an	
The sign applicati	-on method on. Some sig	determi gn-on m	nes hov ethods	w a user si require ad	gns into and manag ditional configurati	ges their ci on in the 3	redentials ^{3rd} party ap	for an pplicat	ion.
The sign application Application	-on method on. Some sig	determi gn-on m e is dete	nes hov ethods ermined	w a user si require ad I by the us	gns into and manag ditional configurati er profile mapping.	es their cl on in the 3 Configure	redentials B rd party ap profile ma	for an pplicat apping	ion.
The sign applicati Applicati	-on method on. Some sig on usernam	determi gn-on m e is dete	nes hov ethods rmined	w a user si require ad I by the us	gns into and manag ditional configurati er profile mapping.	es their clon in the 3	redentials B rd party ap profile ma	for an pplicat apping	ion.
The sign application Application	-on method on. Some sig on usernam enID Connec	determi gn-on m e is dete t	nes hov ethods rmined	w a user sig require ad I by the us	gns into and manag ditional configuration er profile mapping.	ges their close their close their close the second se	redentials ^{grd} party ap profile ma	for an pplicat apping	ion.
The sign application Application Ope	-on method on. Some sig on usernam enID Connec	determi gn-on m e is dete t	nes hov ethods rmined	w a user si require ad I by the us	gns into and manag ditional configurationer profile mapping.	ges their cr on in the 3 Configure	redentials 3 rd party ap profile ma	for an oplicat apping	ion.
The sign application Application Ope	-on method on. Some sig on usernam enID Connec Client ID	determi gn-on m e is dete t	nes hov ethods rmined	w a user si require ad I by the us	gns into and manag ditional configurations er profile mapping.	ges their cl	redentials 3 rd party ap profile ma	for an pplicat apping	ion.
The sign application Application Ope	-on method on. Some sig on usernam enID Connec Client ID	determi gn-on m e is dete t	nes hov ethods rmined	w a user si require ad I by the us	gns into and manag Iditional configuration er profile mapping. Ooaw5qffaqKV	ges their cross on in the 3 Configure	redentials 3 rd party ap profile ma	for an pplicat apping	ion.
The sign application Application Ope	-on method on. Some sig on usernam enID Connec Client ID	determi gn-on m e is dete t	nes hov ethods rmined	w a user si require ad I by the us	gns into and manag ditional configurations er profile mapping. Ooaw5qffaqKV Public identifier f	ges their cl on in the 3 Configure Vje8fS5d6 for the clie	redentials g rd party ap profile ma ent that is p	for an pplicat apping	ion.
The sign application Application Ope	-on method on. Some sig on usernam enID Connec Client ID	determi gn-on m e is dete t	nes hov ethods rmined	w a user si require ad I by the us	gns into and manag Iditional configuration er profile mapping. Ooaw5qffaqKV Public identifier f OAuth flows.	ges their cl on in the 3 Configure Vje8fS5d6 for the clie	redentials g rd party ap profile ma	for an pplicat apping	ion.
The sign application Application Ope	-on method on. Some sig on usernam enID Connec Client ID Client sec	determi gn-on m e is dete t	nes hov ethods rmined	w a user si require ad I by the us	gns into and manag ditional configurations er profile mapping. Ooaw5qffaqKV Public identifier f OAuth flows.	ges their cr on in the 3 Configure Vje8fS5d6 for the clie	redentials g rd party ap profile ma	for an pplicat apping require	ed for all
The sign application Application Ope	-on method on. Some sig on usernam enID Connec Client ID Client sec	determi gn-on m e is dete t	nes hov ethods rmined	w a user si require ad I by the us	gns into and manag ditional configurations er profile mapping. Ooaw5qffaqKV Public identifier f OAuth flows.	ges their cr on in the 3 Configure Vje8fS5d6 for the clie	redentials g rd party ap profile ma ent that is p	for an pplicat apping require	ed for all
The sign application Application Ope	-on method on. Some sig on usernam enID Connec Client ID Client sec	determi gn-on m e is dete t	nes hov ethods rmined	w a user si require ad I by the us	gns into and manag ditional configurations er profile mapping. Ooaw5qffaqKV Public identifier for OAuth flows. Secret used by the authorization coordinates	ges their cr on in the 3 Configure Vje8fS5d6 for the clie the client to de for a to	redentials grd party ap profile ma ent that is n perchange ken. This n	for an pplicat apping require	e kept
The sign application Application Ope	-on method on. Some sig on usernam enID Connec Client ID Client sec	determi gn-on m e is dete t	nes hov ethods rmined	w a user si require ad I by the us	gns into and manag ditional configurations er profile mapping. Ooaw5qffaqKV Public identifier for OAuth flows. Secret used by the authorization coor confidential! Do rest	ges their cr on in the 3 Configure Vje8fS5d6 for the clie the client to de for a tol not include	redentials grd party ap profile ma ent that is n exchange ken. This n e it in apps	for an pplicat apping require e an nust b s which	e kept

6. When you complete the previous step, you'll be authenticated and redirected to Worklytics. If everything went OK, you'll see a new entry in the "Identity Providers" section of the Single Sign-On tab, and your end users can log into Worklytics from the login page using their email address, or by clicking on the Worklytics App Tile they'll get in their Okta's end-user dashboard.

If any doubts, contact our support team.